INFRARED LASER DIODE

DL-LS2075

SANYO

Ver.1 Apr. 2005

Features


- Lasing wavelength : 808 nm (Typ.)
- Single longitudinal mode
- High output power : 200 mW at 50°C
- Low threshold current : Ith = 40 mA (Typ.)
- Fundamental transverse mode
- Package : ø5.6mm


Applications

- Solid state laser pumping


Package

Tolerance : ± 0.2
(Unit : mm)





Pin Connection



Absolute Maximum Ratings

(Tc=25°C)

Parameter		Symbol	Ratings	Unit
Light Output	CW	Po	210	mW
Reverse Voltage	Laser	VR	2	V
	PD		30	
Operating Temperature		Topr	-10 to +50	°C
Storage Temperature		Tstg	-40 to +85	°C

Electrical and Optical Characteristics 1) 2)

(Tc=25°C)

Parameter		Symbol	Condition	Min.	Typ.	Max.	Unit
Threshold Current		Ith	CW	-	40	60	mA
Operating Current		Iop	Po=200mW	-	230	260	mA
Operating Voltage		Vop	Po=200mW	-	2.0	2.4	V
Lasing Wavelength *		Lp	Po=200mW	798	808	818	nm
Beam Divergence 3)	Perpendicular	Qv	Po=200mW	12	16	20	°
	Parallel	Qh	Po=200mW	6	8	10	°
Off Axis Angle	Perpendicular	dQv	-	-3	-	3	°
	Parallel	dQh	-	-3	-	3	°
Differential Efficiency		SE	-	0.8	1.2	-	mW/mA
Monitoring Output Current		Im	Po=200mW	0.15	0.4	0.8	mA

1) Initial values 2) All the above values are evaluated with Tottori Sanyo's measuring apparatus
3) Full angle at half maximum

Note : The above product specification are subject to change without notice.

Tottori SANYO Electric Co., Ltd. Photonics Business Unit
5-318, Tachikawa, Tottori 680-8634 Japan TEL : +81-857-21-2137 FAX : +81-857-21-2161