All rights are reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.
©N.V. PHILIPS' ELECTRONICS
5722 600 20173
Alle rechten voorbehouden. Verveelvoudiging, geheel of gedeeltelijk is niet toegestaan dan met schriftelijke toestemming van de auteursrechthebbende.

Datasheet Plastic Collimator Lens CSX122

These data concern a full plastic spherical plano-convex lens. It is specified for use as a collimator in combination with a diode laser. It can be mounted by use of glue or spring-loaded. Mechanical lock-mounting is not advisable because of possible distortions.

Parameters		**Wavelength**		**Unit**
		670 nm	**785 nm**	
Design conditions				
N.A.		0.12		--
Clear Aperture *CA*		3.0		mm
Designed with laser cover glass (*BK7*) on source side:				
Distance from source		0.55		mm
Glass thickness		0.25		mm
Optical parameters				
Focal Length		12.10	12.22	mm
Back Focal Length *BFL (with 0.25 mm laserglass)*		11.38	11.50	mm
Free Working Distance *FWD*		10.35	10.47	mm
RMS mean	on axis	90		mλ
RMS max. (±3σ)	on axis	95		mλ
	total	95		mλ
Optical Tolerance		0.1		mm
Field Radius		0.3		mm
Mechanical parameters				
Mounting hole diameter D_{mh}		∅ 6.28		mm
Other parameters: see drawing				
Environmental stability				
Storage Temperature		-25 to 100		°C
Operating Temperature		-10 to 75		°C

General Data:
Transmission [%]: 90
Lens Material: Polycarbonate

Specifications subject to change without notice.
Zemax catalogue file available.

PHILIPS